

Data Sheet



4 Series

Electrical Insulating Resin

This 3M Scotchcast resin is a two-part epoxy insulating and encapsulating resin packaged in three sizes. Use 3M Scotchcast resin to splice solid dielectric and oil-filled cables up to **8 kV** - and to jacket high-voltage splices through **69 kV**. Flash point: 140°C/300°F or higher. It is included in the 3M 82 and 90-B1 series splice kits.



Product	UPC	Size/Type of package	Case Qty.
4	25677	A/3.2 oz. (90g) 4.8 cu. in. (12.2 cu. cm)	10
4	25685	B/7.4 oz. (209g) 11.2 cu. in. (28.4 cu. cm)	10
4	25693	C/14.7 oz. (418g) 22.3 cu. in. (56.6 cu. cm)	10

IMPORTANT NOTICE TO PURCHASER:
All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

All statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECTOR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS.

© 3M 1993

3M Electrical Products Division

6801 River Place Blvd.
Austin, Texas 78726 - 9000

